




Item name:	VWJK04	Pictures: 
Fabric:	100% polyester 300D Oxford PU coated	
Lining:	100% polyester taffeta, 190T	
Padding:	100% polyester quilted lining, 180gsm	
Reflective fabric:	Backing: 100% polyester with coating (glass micro-beads), 50mm cutting, grey color Washing at 40°C cycles 25, dry cleaning cycles 5	
Color:	Hi visibility yellow; Hi visibility orange	
Features:	Waterproof taped seams Studded front flap, and a concealed hood One cell phone pocket on right chest Two easy access lower pockets Elasticated hem and cuff for enhanced weather proofing Zipped access on lining for logo printing or embroidery	

Size guide(cm)

	Garment Size (Tol.+3/-2) cm	S	M	L	XL	XXL	XXXL
	A. to fit body length(cm)	156-164	164-172	172-180	180-188	188-196	196-204
	B. to fit chest width(cm)	86-94	94-102	102-110	110-118	118-129	129-141



Washing instruction:	
-----------------------------	---

Packing:	1pc in polybag with EAN code sticker, 10pcs in each carton. Carton Size: S-M:64*41*34cm, L-XL:66*42*34cm, 2XL-3XL:70*43*34cm
-----------------	---

Certification

Fabric:	EN ISO20471:2013; EN343:2003+A1:2007 Class 3 1
----------------	--

Reflective Tape:	EN ISO20471:2013;
-------------------------	-------------------

Garment:																																						
EN ISO 20471 	<table border="1"> <tr> <th>Performance class of garment</th> <th colspan="3">Class</th> <th>Classification</th> </tr> <tr> <td>Minimum materials</td> <td>3</td> <td>2</td> <td>1</td> <td rowspan="3">EN ISO 20471 Class 3</td> </tr> <tr> <td>Background material(m2)</td> <td>0.8</td> <td>0.5</td> <td>0.14</td> </tr> <tr> <td>Retroreflective material(m2)</td> <td>0.2</td> <td>0.13</td> <td>0.1</td> </tr> </table>	Performance class of garment	Class			Classification	Minimum materials	3	2	1	EN ISO 20471 Class 3	Background material(m2)	0.8	0.5	0.14	Retroreflective material(m2)	0.2	0.13	0.1																			
	Performance class of garment	Class			Classification																																	
	Minimum materials	3	2	1	EN ISO 20471 Class 3																																	
	Background material(m2)	0.8	0.5	0.14																																		
Retroreflective material(m2)	0.2	0.13	0.1																																			
EN343:2003+A1:2007 	<table border="1"> <tr> <th>Resistance to water penetration</th> <th colspan="3">Class</th> <th>Classification</th> </tr> <tr> <td>Test to be made</td> <td>1</td> <td>2</td> <td>3</td> <td rowspan="3">EN343 Class 3</td> </tr> <tr> <td>Before pretreatment</td> <td>wp≥8000pa</td> <td>no test</td> <td>no test</td> </tr> <tr> <td>Seams before pretreatment</td> <td>wp>8000pa</td> <td>wp≥8000pa</td> <td>wp≥13000pa</td> </tr> <tr> <td>After every pretreatment</td> <td>no test</td> <td>wp>8000pa</td> <td>wp≥13000pa</td> <td></td> </tr> <tr> <td>Water vapour resistance</td> <th colspan="3">Class</th> <th>Classification</th> </tr> <tr> <td></td> <td>1</td> <td>2</td> <td>3</td> <td rowspan="2">EN343 Class 1</td> </tr> <tr> <td>R_{et}(m².Pa/w)</td> <td>R_{et}>40</td> <td>20<R_{et}≤40</td> <td>Ret≤20</td> </tr> </table>	Resistance to water penetration	Class			Classification	Test to be made	1	2	3	EN343 Class 3	Before pretreatment	wp≥8000pa	no test	no test	Seams before pretreatment	wp>8000pa	wp≥8000pa	wp≥13000pa	After every pretreatment	no test	wp>8000pa	wp≥13000pa		Water vapour resistance	Class			Classification		1	2	3	EN343 Class 1	R _{et} (m ² .Pa/w)	R _{et} >40	20<R _{et} ≤40	Ret≤20
	Resistance to water penetration	Class			Classification																																	
	Test to be made	1	2	3	EN343 Class 3																																	
	Before pretreatment	wp≥8000pa	no test	no test																																		
	Seams before pretreatment	wp>8000pa	wp≥8000pa	wp≥13000pa																																		
	After every pretreatment	no test	wp>8000pa	wp≥13000pa																																		
Water vapour resistance	Class			Classification																																		
	1	2	3	EN343 Class 1																																		
R _{et} (m ² .Pa/w)	R _{et} >40	20<R _{et} ≤40	Ret≤20																																			

This product has been certified by Centexbel, Notified body number:0493 in accordance with Article 10 of PPE Directive 89/686/EEG to comply with the standards: EN13688:2013; EN ISO20471:2013 Class 3; EN343:2003+A1:2007 Class 3 1.